

Noah

8series
SPECIALTY N-860Z
N-862Zp



1-310-323-1134
www.timbucktoomfg.com
www.tmiusa.net

Flood Recovery & Restoration / Automatic Dumping Machine

Designed to move/pump out liquid, sludge, and solids up to 3/8" diameter

Manufacturer of commercial & environmental cleaning equipment

© 2011 TIMBUCKTOO MFG., INC.

The Noah-860Z & N-862Zp (flood control & water damage machine) can drain a full swimming pool to the smallest spill on a floor.

60 (max) gallon per minute dumping capacity. (one gallon per second)

Specifications: (N-860Z)

- ~ heavy duty fiber composite body
- ~ one 3 stage vacuum motor
- ~ 140" suction power (H2O)
- ~ air flow 107 (cfm)
- ~ flow rate 60 gpm (one gallon per second max)
- ~ 120 volt AC with 18 amperes (MAX 20 amp.)
- ~ 20 gallon recovery tank
- ~ easy access to all mechanical components
- ~ exterior dimensions H 32" x W 16" x L 21"
- ~ stationary handle
- ~ 50' x 1-1/2 ID. vacuum hose and 50' dump hose
- ~ 25' 12-3 power cord
- ~ ground fault circuit interrupter
- ~ 14.5" double squeegee pick up wand
- ~ stainless steel lids
- ~ 2 / 4" non-marking casters & 2 / 12" rear wheels
- ~ shipping weight 100lb.



Options/ Accessories:

- ~ additional dump hose with quick locking connection
- ~ additional vacuum hose with hose mender
- ~ acoustic muffling system
- ~ multitude of squeegee pick up wands



Specifications: (N-862Zp)

- ~ two 3 stage vacuum motor
- ~ 140" suction power (H2O)
- ~ air flow 213 (cfm)
- ~ 2 parallel vacuum motors
- ~ 2 G.F.C.I.
- ~ 120 volt AC with 25 amperes (MAX 35 amp.)
- ~ two 25' cord



NOTE: * some options may not be used with standard specifications.
* hose length can be added 5 ft. increments up to 50 ft. per length.

standard color: blue
CAUTION: Do not use flammable and volatile material.