

Symphony ^{HARD SURFACE} 300 _{SOFT SURFACE} series




1-310-323-1134
 www.timbucktoomfg.com
 www.tmiusa.net

A professional, compact truckmount carpet and hard surface cleaning machine, which is simple, powerful and economic. Powered by Kohler 18 horse power engine. Pump is 1500 psi adjustable & blower is sutorbilt 36, with easy access for all maintenance needs. Stainless steel is our product of choice to provide performance and long life.

Manufacturer of commercial & environmental cleaning equipment

© 2011 TIMBUCKTOO MFG., INC.

Specifications: (S395)

- ~ kohler 18 horse power with low oil shut down engine
- ~ vacuum (#36 blower)
- ~ dimension (H21" x W32" x L29")
- ~ triple vacuum filtering system
- ~ vacuum safety valve
- ~ 1500 PSI / 3.0 GPM
- ~ electric clutch for pump
- ~ easy access for lubrication & maintenance
- ~ adjustable chemical feed system
- ~ tachometer
- ~ pressure gauge
- ~ hour meter
- ~ heating system (s/s heat exchanger) 
- ~ pressure safety valve
- ~ 100' vacuum and solution hose
- ~ 3/8" ID x 50' water supply line
- ~ 14 PC faucet adapter kit
- ~ 40 gallon recovery tank (stainless steel)
- ~ 12" 3000psi Auto-Seal Wand
 (heavy duty self adjustable suction angle head with adjustable stainless steel grip handle, double bend 3000 PSI valve, by pass, 2 jets, stainless steel line and grip handle)



picture shown with optional storage reel and standard 100' hose

picture shown 12" Auto-Seal Wand, 3000 psi valve, 2 jets with grip (standard)

picture shown S395

Options:

- ~ vacuum gauge
- ~ hose storage reel
- ~ live vacuum hose reel
- ~ live solution hose reel
- ~ pre-spray system
- ~ other attachments available-hand tools, wands, stone & grout tools



picture shown optional counter top/wall 3000psi SQ wand



picture shown optional H.S. stainless steel by-pass hand tool



picture shown S395 with 40 gallon recovery tank

CAUTION: Do not use flammable and volatile material.