

Powerful portable extractor, constructed with heavy duty fiber composite body, stainless steel lid and handle.

Manufacturer of Commercial & Environmental Cleaning Equipment

© 2018 TIMBUCKTOO MFG, INC.

## Specifications: (I-5XG)

#### Motor

(3) 2 Stage vacuum motors[Part #: 11639200]

249" Water lift

110 CFM Air flow

### **Pump**

500 PSI pump

2.1 GPM Flow rate

## **Power**

120 Volt AC / 17.5/11.5 Amps max

(2) 25' 12/3 Gauge power cords

## Capacity

15 Gallon solution tank and 14 gallon recovery tank

## **Accessories Included:**

(1) 25' vacuum hose & 25' solution hose assembly [TA1532550-4MF]

(1) Single jet, 12", Autoseal Wand [Part #: WMPT1V11008JG] (Patented heavy duty self-adjustable suction angle head with adjustable stainless steel grip handle)

(1) Stationary handle

## **Options:**

Available with 1500 PSI pump

Multiple vacuum motors available

Output female plug

GFCI (ground fault circuit interrupter)

Side handle

Chemical feed and mixing system

Auto fill and Auto dump systems

Acoustic muffling system (selected models only)

Other Autoseal Wands available

Other hand tools and accessories available

Intank heater with 140° F preset thermostat 🖚

For any specific custom options please contact customer service for availability

standard accessories: (2) 12" rear wheels (2) 3" swivel casters

Picture shown with

**Since 1974** 

## **Shipping Weight** 160 lbs +

Picture shown with

standard accessories: (1) 25' vac hose & 25' sol hose.

(1) single jet, 12", Autoseal Wand with stainless steel grip handle.

Optional: chemical feed system, auto dump system, and auto fill system.

## **Exterior Dimensions**

H 33" x W 20" x L 25"

## **Standard Colors**

Blue and red

Custom colors available please call customer service



Comparison sheet in the back

# **Infinity Series**



# **Soft Surface**

Infinity Models				Compare to	
Model	I-5XG	I-4	I-5	Mustang (M-12)	Mustang (M-22)
Vacuum Motor	(3) 2 Stage	(2) 2 Stage	(2) 2 Stage	(2) 2 Stage	(3) 2 Stage
Water Lift	249"	228"	249"	143"	249"
Air Flow	110 CFM	99 CFM	107 CFM	107 CFM	108 CFM
		Pu	ımps		
60 PSI - TMI Brand	0	0	0	0	0
100 PSI - Shurflo	0	S	0	0	S
120 PSI - TMI Brand	0	0	0	S	0
170 PSI - TMI Brand	0	0	0	0	0
220 PSI - TMI Brand	0	0	0	0	0
500 PSI - Pumptec	S	0	S	0	0
500 PSI - Cat Pump	S	0	S	0	0
		Po	wer		
120 Volts	S	S	S	S	S
240 Volts	0	0	0	0	0
Max Amps	17.5/11.5	17.5	17.5	17.5	17.5/8.5
-	Va	cuum/Soluti	on Hose Len	gths	
10 ft / 10 ft	-	-	-	-	-
15 ft / 15 ft	-	-	-	-	-
25 ft / 25ft	S	S	S	S	S
50 ft / 50 ft	0	0	0	0	0
		W	ands	,	
Autoseal 1-Jet	S	S	S	S	S
Autoseal See Throu 1-Jet	0	0	0	0	0
Autoseal Double Bend 1-Jet	0	0	0	0	0
Autoseal 2-Jet	0	0	0	0	0
Autoseal See Throu 2-Jet	0	0	0	0	0
Autoseal Double Bend 2-Jet	0	0	0	0	0
		Wheels a	nd Casters		
(4) 3 " Casters	0	0	0	0	0
(2) 3" Casters and (2) 12" Rear Wheels	S	S	S	0	0
(2) 3 " Casters and (2) 10" Rear Wheels	0	0	0	S	S
		Other	Options		
Intank Heater	0	0	0	0	0
Inline Heater	0	0	0	0	0
Stationary Handle	S	S	S	S	S
		Dimension	s and Weight		
Solution / Recovery Tank Capacity	15/14 Gallon	15/14 Gallon	15/14 Gallon	17/15 Gallon	17/15 Gallon
Dimensions of Machine Only	33"x20"x25"	33"x20"x25"	33"x20"x25"	40"x 21" x 31"	40"x 21" x 31"
Weight of Machine Only	148 lb	108 lb	108 lb	201 lb	
Shipping Dimensions of Machine and Hose	35"x20"x27"	35"x20"x27"	35"x20"x27"	42" x 25" x 34"	42" x 25" x 34"
Shipping Weight of Machine and Hose	160 lb	120 lb	120 lb	286 lb	
Shipping Dimensions of Wand	13"x13"x66"	13"x13"x66"	13"x13"x66"	13"x13"x66"	13"x13"x66"
Shipping Weight of Wand	13 lb	13 lb	13 lb	13 lb	13 lb